

THOMSON

DELPHION

RESEARCH

[Log Out](#) [Work Files](#) [Saved Searches](#) [My Account](#) | [Products](#)

PRODUCTS

INSIDE DELPHION

Search: Quick/Number Boolean Advanced Derwent

The Delphion Integrated View

Get Now: PDF | [More choices...](#)

Tools: Add to Work File: [Create new W](#)

View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent](#)

 [E](#)

>Title: **JP8249849A2: FLOATING MAGNETIC HEAD DEVICE**

Derwent Title: Levitating-type magnetic head for hard-disk drive - has suspension covered with insulated coating of 10-50 nanometer thickness, which supports magnetic head
[\[Derwent Record\]](#)

Country: **JP Japan**
 Kind: **A**

Inventor: **SATO TERUYA;**

Assignee: **SONY CORP**
[News, Profiles, Stocks and More about this company](#)



Published / Filed: **1996-09-27 / 1995-03-15**

Application Number: **JP1995000056061**

IPC Code: **G11B 21/21;**

Priority Number: **1995-03-15 JP1995000056061**

Abstract: PURPOSE: To obtain a floating magnetic head device capable of lessening the damage of a magnetic head element even in the case of the receipt of the electric discharge from an external material to be electrified.

CONSTITUTION: The floating sliding surface 2 of the magnetic head slider of the magnetic head 3 and a hard disk come into contact with when starting and stopping. The floating sliding surface 2 is floated and run at a micro-sapcing on a hard disk surface by the stationary flow of the air generated on the surface of the hard disk rotating at a high speed. A suspension 1 supports the magnetic head 3 and is fixed to an actuator. A signal conductor part 7 transmits the signals to the magnetic head 3 and the signals from the magnetic head 3. This suspension 1 is coated with an insulating film having a thickness of 10 to 50nm and the signal conductor part 7 is coated with an insulating film having a thickness of 0.006 to 0.01mm.

COPYRIGHT: (C)1996,JPO

Family: None

Other Abstract Info: **DERABS G96-490459 DERG96-490459**



Nominate



[this for the Gallery...](#)